


# Computer Memory Test Labs Final Report

<u>MOTHERBOARD</u>	<u>MANUFACTURER</u>	<u>CHIPSET</u>	<u>TEST NUMBER</u>	<u>TEST STATUS</u>
		<u>MODULE INFORMATION</u>		<u>Compatibility Ranking Level</u>
Manufacturer Name: Part #: MB: Config: DRAM: DRAM Part #: PCB Part: PCB_layer_count: Module Info:			<div style="border: 1px solid black; padding: 5px; display: inline-block;"> <b>Certified CRL</b>   </div> Cas Latency: Dual Die Package: <input type="checkbox"/> Env. Code Bank: Assembly Type:	
<u>SYSTEM INFORMATION</u>			<u>TESTING DETAILS</u>	
<u>MINIMUM SYSTEM INFORMATION</u> Minimum System: Serial Number: Board Revision: Post Memory Count: Processor Code: Bios at time of test: MCFT Memory Count: Max_HDD_Man: Max_HDD_Cap: Max_HDD_Ser:  <u>MAXIMUM SYSTEM INFORMATION</u> Maximum System: Serial Number: Board Revision: Post Memory Count: Processor Code: Bios at time of test: MCFT Memory Count: Max_HDD_Man: Max_HDD_Cap: Max_HDD_Ser:			55°C Temperature: Standard Voltage Start Date: Stop Date: Insertion Test: SPD Check: MCFT Min: MCFT Max: S3 Test: Power Cycle Test: Power Cycle Time: OS: Service Pack: Test Version:	
<u>VENDOR CONTACT INFORMATION</u>				
Contact:		Contact Phone:		Purchase Order #:
Test Traveler Notes:			CMTL USE ONLY:	
			Verified by:  Emailed by:	

Test Technician:

In the event of a module failure, CMTL is not required to provide root cause analysis. Accuracy of testing is restricted to the above mentioned module with specific DRAM, PCB and other components as listed and tested with the CMTL Memory Compatibility. Functionality Test, Microsoft Advanced Server 2000®, Windows NT 4.0 Enterprise Edition®, Windows XP®, Windows 98 SE®, Dos 6.22®, MSTRESS® (v x.x), XLINEAR® (v x.xx), FXLINEAR® (v x.xx), Patin® (v x.x), WinMTA® (v x.xx). (Voltage margining applied only to those systems that are applicable.)

[WWW.CMTLABS.COM](http://WWW.CMTLABS.COM)