

Computer Memory Test Labs Final Report

<u>MOTHERBOARD</u>	<u>MANUFACTURER</u>	<u>CODE NAME</u>	<u>TEST NUMBER</u>	<u>TEST STATUS</u>
D865GLC/D865GBF	Intel	La Crosse	003401	PASSED

MODULE INFORMATION

Manufacturer Name: **Buffalo**
 Part #: **DD333-512/SD**
 MB: **512MB**
 Config: **64M x 64**
 DRAM: **Samsung**
 DRAM Part #: **K4H560838D-TCB3 rev D**
 PCB Part: **UE0532-AA**
 PCB_layer_count: **6 Layer**
 Module Info: **Unbuffered Non-ECC 333Mhz DDR DIMM**
 Cas Latency: **2.5**
 Assembly Type: **Single Board/Non Stacked**

SYSTEM INFORMATION

TESTING DETAILS

MINIMUM SYSTEM INFORMATION

Minimum System: LaCrosse
 Post Memory Count: 512
 Processor Code: P4 2.66GHz
 Bios at time of test: BF86510A.86A.0013.B04 1
 MCFT Memory Count: 512

MAXIMUM SYSTEM INFORMATION

Maximum System: LaCrosse
 Post Memory Count: 2048
 Processor Code: P4 2.66GHz
 Bios at time of test: BF86510A.86A.0013.B04 2
 MCFT Memory Count: 2048

55°C Temperature: Standard Voltage

Start Date: 3/25/2003
 Stop Date: 3/26/2003
 Insertion Test: Pass
 SPD Check: Pass
 MCFT Min: Pass
 MCFT Max: Pass
 S3 Test: Pass
 Power Cycle Test: Pass
 Power Cycle Time: 30

VENDOR CONTACT INFORMATION

Contact: Tim Juarez Contact Phone: Purchase Order #:

Test Traveler Notes:

CMTL USE ONLY:

Verified by:

Emailed by:

Test Technician: David Sandstrom

In the event of a module failure, CMTL is not required to provide root cause analysis. Accuracy of testing is restricted to the above mentioned module with specific DRAM, PCB and other components as listed and tested with the CMTL Memory Compatibility Functionality Test, Microsoft Advanced Server 2000®, Windows NT 4.0 Enterprise Edition®, Windows XP®, Windows 98 SE®, Dos 6.22®, MSTRESS® (v x.x), XLINEAR® (v x.xx), FXLINEAR® (v x.xx), Patin® (v x.x), WinMTA® (v x.xx). (Voltage margining applied only to those systems that are applicable.)

WWW.CMTLABS.COM