

Computer Memory Test Labs Final Report

<u>MOTHERBOARD</u>	<u>MANUFACTURER</u>	<u>CHIPSET</u>	<u>TEST NUMBER</u>	<u>TEST STATUS</u>
D865GLC/D865GBF	Intel	Intel 865G	005477	PASSED

<u>MODULE INFORMATION</u>				
Manufacturer Name: Buffalo				
Part #: DD266-A1G/SD				
MB: 1GB				
Config: 128M x 64				
DRAM: Samsung				
DRAM Part #: K4H560438D-TCB0 rev D				
PCB Part: UE0502-AA				
PCB_layer_count: 6 Layer				
Module Info: Unbuffered Non-ECC 266Mhz DDR DIMM				
Cas Latency: 2.5				
Assembly Type: Stacked DRAM				

<u>SYSTEM INFORMATION</u>	<u>TESTING DETAILS</u>
<p><u>MINIMUM SYSTEM INFORMATION</u></p> <p>Minimum System: La Crosse Post Memory Count: 1016 Processor Code: P4 2.60C Bios at time of test: BF86510A.86A.0043.P09 1 MCFT Memory Count: 1016</p> <p><u>MAXIMUM SYSTEM INFORMATION</u></p> <p>Maximum System: La Crosse Post Memory Count: 3680 Processor Code: P4 2.60C Bios at time of test: BF86510A.86A.0043.P09 2 MCFT Memory Count: 3680</p>	<p>55°C Temperature: Standard Voltage</p> <p>Start Date: 10/29/2003 Stop Date: 10/30/2003</p> <p>Insertion Test: Pass SPD Check: Pass MCFT Min: Pass MCFT Max: Pass S3 Test: Pass Power Cycle Test: Pass Power Cycle Time: 28</p>

<u>VENDOR CONTACT INFORMATION</u>	
Contact: Tim Juarez	Contact Phone: Purchase Order #:
Test Traveler Notes:	CMTL USE ONLY:
Legacy USB disabled. 8MB shared for onboard video.	Verified by: Emailed by:

Test Technician: Keith Patton

In the event of a module failure, CMTL is not required to provide root cause analysis. Accuracy of testing is restricted to the above mentioned module with specific DRAM, PCB and other components as listed and tested with the CMTL Memory Compatibility Functionality Test, Microsoft Advanced Server 2000®, Windows NT 4.0 Enterprise Edition®, Windows XP®, Windows 98 SE®, Dos 6.22®, MSTRESS® (v x.x), XLINEAR® (v x.xx), FXLINEAR® (v x.xx), Patin® (v x.x), WinMTA® (v x.xx). (Voltage margining applied only to those systems that are applicable.)

WWW.CMTLABS.COM