

# Computer Memory Test Labs Final Report

<u>MOTHERBOARD</u>	<u>MANUFACTURER</u>	<u>CHIPSET</u>	<u>TEST NUMBER</u>	<u>TEST STATUS</u>
D915GAV/D915GAG/D915PSY/D915PGN	Intel	Intel 915G	007627	PASSED

<u>MODULE INFORMATION</u>				
Manufacturer Name: <b>Legend</b>				
Part #: <b>L6464DC6-BU1HDC5D</b>				
MB: <b>512MB</b>				
Config: <b>64M x 64</b>				
DRAM: <b>Hyundai</b>				
DRAM Part #: <b>HY5DU56822DT-J rev D</b>				
PCB Part: <b>B6U808 rev 1</b>				
PCB_layer_count: <b>6 Layer</b>				
Module Info: <b>Unbuffered          Non-ECC          333Mhz          DDR DIMM</b>				
Cas Latency: <b>2.5</b>				
Assembly Type: <b>Single Board/Non Stacked</b>				

<u>SYSTEM INFORMATION</u>	<u>TESTING DETAILS</u>
<p><b><u>MINIMUM SYSTEM INFORMATION</u></b></p> <p>Minimum System: AvAlon/Augsburg            Post Memory Count: 511            Processor Code: P4 3.2GHz 800MHz            Bios at time of test: EV91510.86A.0008.2004.0322 5-29            MCFT Memory Count: 510</p> <p><b><u>MAXIMUM SYSTEM INFORMATION</u></b></p> <p>Maximum System: Avalon/Augsburg            Post Memory Count: 2044            Processor Code: P4 3.2GHz 800MHz            Bios at time of test: EV91510.86A.0008.2004.0322 5-29            MCFT Memory Count: 2046</p>	<p>55°C Temperature: Standard Voltage</p> <p>Start Date: 8/19/2004            Stop Date: 8/20/2004            Insertion Test: Pass            SPD Check: Pass            MCFT Min: Pass            MCFT Max: Pass            S3 Test: Pass            Power Cycle Test: Pass            Power Cycle Time: 31</p>

<u>VENDOR CONTACT INFORMATION</u>	
Contact:	Contact Phone:          Purchase Order #: 311135
Test Traveler Notes:	<b>CMTL USE ONLY:</b>
	Verified by:
	Emailed by:

Test Technician: Sonni Nguyen

In the event of a module failure, CMTL is not required to provide root cause analysis. Accuracy of testing is restricted to the above mentioned module with specific DRAM, PCB and other components as listed and tested with the CMTL Memory Compatibility Functionality Test, Microsoft Advanced Server 2000®, Windows NT 4.0 Enterprise Edition®, Windows XP®, Windows 98 SE®, Dos 6.22®, MSTRESS® (v x.x), XLINEAR® (v x.xx), FXLINEAR® (v x.xx), Patin® (v x.x), WinMTA® (v x.xx). (Voltage margining applied only to those systems that are applicable.)

[WWW.CMTLABS.COM](http://WWW.CMTLABS.COM)