

Computer Memory Test Labs Final Report

<u>MOTHERBOARD</u>	<u>MANUFACTURER</u>	<u>CHIPSET</u>	<u>TEST NUMBER</u>	<u>TEST STATUS</u>
D925XEBC2/D925XECV2	Intel	Intel D925XE	009558	PASSED
<u>MODULE INFORMATION</u>				
Manufacturer Name: Wintec Industries Part #: 39134281 MB: 1GB Cas Latency: 4 Config: 128M x 64 Assembly Type: Single Board/Non Stacke DRAM: Infineon DRAM Part #: HYB18T512800AF37 rev A PCB Part: D2U872 na PCB_layer_count: 6 Layer Module Info: Unbuffered Non-ECC 533Mhz DDR2 DIMM				
<u>SYSTEM INFORMATION</u>			<u>TESTING DETAILS</u>	
<u>MINIMUM SYSTEM INFORMATION</u>				
Minimum System:	D925XEBC2/D925XECV2	05-31	55°C Temperature: Standard Voltage	
Serial Number:	BTBC44301389		Start Date: 6/29/2005	
Board Revision:	C85639-204		Stop Date: 7/1/2005	
Post Memory Count:	1024		Insertion Test: Pass	
Processor Code:	P4 3.6Ghz 800Mhz		SPD Check: Pass	
Bios at time of test:	CV92510A.86A.0338.2004		MCFT Min: Pass	
MCFT Memory Count:	1023		MCFT Max: Pass	
Max_HDD_Man:	MAXTOR		S3 Test: Pass	
Max_HDD_Cap:	40GB		Power Cycle Test: Pass	
Max_HDD_Ser:	WMAD1147172		Power Cycle Time: 34	
<u>MAXIMUM SYSTEM INFORMATION</u>				
Maximum System:	D925XEBC2/D925XECV2	05-31	OS: Windows	
Serial Number:	BTBC44301494		Service Pack: NA	
Board Revision:	C85639-204		Test Version: MCFT 2.24	
Post Memory Count:	3584			
Processor Code:	P4 3.6Ghz 800Mhz			
Bios at time of test:	CV92510A.86A.0338.2004			
MCFT Memory Count:	3583			
Max_HDD_Man:	MAXTOR			
Max_HDD_Cap:	40GB			
Max_HDD_Ser:	WMAD1147172			
<u>VENDOR CONTACT INFORMATION</u>				
Contact:	Contact Phone:	Purchase Order #:		
Bo Zhang	(510) 360-6364	1424704-4		
Test Traveler Notes:			CMTL USE ONLY:	
			Verified by:	
			Emailed by:	

Test Technician: Sonni Nguyen

In the event of a module failure, CMTL is not required to provide root cause analysis. Accuracy of testing is restricted to the above mentioned module with specific DRAM, PCB and other components as listed and tested with the CMTL Memory Compatibility Functionality Test, Microsoft Advanced Server 2000®, Windows NT 4.0 Enterprise Edition®, Windows XP®, Windows 98 SE®, Dos 6.22®, MSTRESS® (v x.x), XLINEAR® (v x.x), FXLINEAR® (v x.x), Patin® (v x.x), WinMTA® (v x.x). (Voltage margining applied only to those systems that are applicable.)

WWW.CMTLABS.COM