


# Computer Memory Test Labs Final Report

<u>MOTHERBOARD</u>	<u>MANUFACTURER</u>	<u>CHIPSET</u>	<u>TEST NUMBER</u>	<u>TEST STATUS</u>
DQ965WC/DG965PZ	Intel	Intel® G965	012226	PASSED
<u>MODULE INFORMATION</u>				<u>Compatibility Ranking Level</u>
Manufacturer Name: <b>ATP Electronics</b> Part #: <b>AJ64K64D8BHE7S</b> MB: <b>512MB</b> Config: <b>64M x 64</b> DRAM: <b>Samsung</b> DRAM Part #: <b>K4T51083QC-ZCE7 rev C</b> PCB Part: <b>SJ240D08K1 na</b> PCB_layer_count: <b>6 Layer</b> Module Info: <b>Unbuffered Non-ECC 800Mhz</b>			<div style="border: 1px solid black; padding: 5px; display: inline-block;"> <b>Certified CRL</b>    <b>9</b> </div> Cas Latency: <b>5</b> Dual Die Package: <input type="checkbox"/> Env. Code <b>RoHS</b> Bank: <b>1</b> Assembly Type: <b>Single Board/Non Stacked</b> <b>DDR2 DIMM</b>	
<u>SYSTEM INFORMATION</u>		<u>TESTING DETAILS</u>		
<u>MINIMUM SYSTEM INFORMATION</u> Minimum System: DQ965WC/DG965PZ Serial Number: LAPZ6260003J Board Revision: D41835-300 Post Memory Count: 512 Processor Code: P4 3.6Ghz 800Mhz Bios at time of test: MQ96510J.86A.1458 MCFT Memory Count 493M 488K Max_HDD_Man: Max_HDD_Cap: Max_HDD_Ser:		55°C Temperature: Standard Voltage Start Date: 10/31/2006 Stop Date: 11/1/2006 Insertion Test: Pass SPD Check: Pass MCFT Min: Pass MCFT Max: Pass S3 Test: N/A Power Cycle Test: N/A Power Cycle Time: OS: N/A Service Pack: N/A Test Version: R.S.T PRO V2.56		
<u>MAXIMUM SYSTEM INFORMATION</u> Maximum System: DQ965WC/DG965PZ Serial Number: LAPZ62600054 Board Revision: D41835-300 Post Memory Count: 2048 Processor Code: P4 3.6Ghz 800Mhz Bios at time of test: MQ96510J.86A.1458 MCFT Memory Count 2021M 500K Max_HDD_Man: Max_HDD_Cap: Max_HDD_Ser:				
<u>VENDOR CONTACT INFORMATION</u>				
Contact: Louis Lau		Contact Phone: (408) 732-5000 x 5		Purchase Order #:
Test Traveler Notes:			CMTL USE ONLY:	
			Verified by:	
			Emailed by:	

Test Technician: Thanh Nguyen

In the event of a module failure, CMTL is not required to provide root cause analysis. Accuracy of testing is restricted to the above mentioned module with specific DRAM, PCB and other components as listed and tested with the CMTL Memory Compatibility Functionality Test, Microsoft Advanced Server 2000®, Windows NT 4.0 Enterprise Edition®, Windows XP®, Windows 98 SE®, Dos 6.22®, MSTRESS® (v x.xx), XLINEAR® (v x.xx), FXLINEAR® (v x.xx), Patin® (v x.x), WinMTA® (v x.xx). (Voltage margining applied only to those systems that are applicable.)

[WWW.CMTLABS.COM](http://WWW.CMTLABS.COM)