




Computer Memory Test Labs Final Report

<u>MOTHERBOARD</u>	<u>MANUFACTURER</u>	<u>CHIPSET</u>	<u>TEST NUMBER</u>	<u>TEST STATUS</u>		
D865GLC/D865GBF/D865GRH	Intel	Intel 865G	012460	PASSED		
<u>MODULE INFORMATION</u>				<u>Compatibility Ranking Level</u>		
Manufacturer Name: Buffalo Part #: DD4333-X256ICJ MB: 256MB Config: 32M x 64 DRAM: Qimonda (Infineon) DRAM Part #: HYB25D512160CE-5 rev C PCB Part: UE0632-AA na PCB_layer_count: 6 Layer Module Info: Unbuffered Non-ECC 400Mhz			Cas Latency: 3 Dual Die Package: <input type="checkbox"/> Env. Code RoHS Bank: 1 Assembly Type: Single Board/Non Stacked DDR DIMM	<table border="1" style="width: 100%;"> <tr> <td style="text-align: center;">Certified CRL</td> </tr> <tr> <td style="text-align: center;"> 1</td> </tr> </table>	Certified CRL	 1
Certified CRL						
 1						
<u>SYSTEM INFORMATION</u>		<u>TESTING DETAILS</u>				
<u>MINIMUM SYSTEM INFORMATION</u> Minimum System: D865GLC/D865GBF/D865GRH Serial Number: IWLC31008955 Board Revision: C32156-403 Post Memory Count: 256 Processor Code: P4 2.53Ghz 533Mhz Bios at time of test: BF86510A.86A.0077.P25 MCFT Memory Count 239M Max_HDD_Man: Max_HDD_Cap: Max_HDD_Ser:		55°C Temperature: Standard Voltage Start Date: 10/23/2006 Stop Date: 10/24/2006 Insertion Test: Pass SPD Check: Pass MCFT Min: Pass MCFT Max: Pass S3 Test: N/A Power Cycle Test: N/A Power Cycle Time: OS: NA Service Pack: NA Test Version: MCFT V2.24				
<u>MAXIMUM SYSTEM INFORMATION</u> Maximum System: D865GLC/D865GBF/D865GRH Serial Number: ABLC31832723 Board Revision: C32156-403 Post Memory Count: 1024 Processor Code: P4 2.53Ghz 533Mhz Bios at time of test: BF86510A.86A.0077.P25 MCFT Memory Count 1007M 256K Max_HDD_Man: Max_HDD_Cap: Max_HDD_Ser:						
<u>VENDOR CONTACT INFORMATION</u>						
Contact: Tim Juarez		Contact Phone:		Purchase Order #:		
Test Traveler Notes:			CMTL USE ONLY:			
			Verified by:			
			Emailed by:			

Test Technician: Thanh Nguyen

In the event of a module failure, CMTL is not required to provide root cause analysis. Accuracy of testing is restricted to the above mentioned module with specific DRAM, PCB and other components as listed and tested with the CMTL Memory Compatibility Functionality Test, Microsoft Advanced Server 2000®, Windows NT 4.0 Enterprise Edition®, Windows XP®, Windows 98 SE®, Dos 6.22®, MSTRESS® (v x.x), XLINEAR® (v x.xx), FXLINEAR® (v x.xx), Patin® (v x.x), WinMTA® (v x.xx). (Voltage margining applied only to those systems that are applicable.)

WWW.CMTLABS.COM