




# Computer Memory Test Labs Final Report

<u>MOTHERBOARD</u>	<u>MANUFACTURER</u>	<u>CHIPSET</u>	<u>TEST NUMBER</u>	<u>TEST STATUS</u>				
DQ965GFE	Intel	Intel® G965	012565	PASSED				
<u>MODULE INFORMATION</u>				<u>Compatibility Ranking Level</u>				
Manufacturer Name: <b>Buffalo</b> Part #: <b>D2U667C-1GMDJ</b> MB: <b>1GB</b> Config: <b>128M x 64</b> DRAM: <b>Micron</b> DRAM Part #: <b>MT47H64M8B6-3 rev D</b> PCB Part: <b>2DUE28F-AA na</b> PCB_layer_count: <b>6 Layer</b> Module Info: <b>Unbuffered      Non-ECC      667Mhz</b>			Cas Latency: <b>5</b> Dual Die Package: <input type="checkbox"/> Env. Code <b>RoHS</b> Bank: <b>2</b> Assembly Type: <b>Single Board/Non Stacked</b> <b>DDR2 DIMM</b>	<table border="1" style="margin: auto;"> <tr> <td style="text-align: center;"><b>Certified</b></td> <td style="text-align: center;"><b>CRL</b></td> </tr> <tr> <td style="text-align: center;"></td> <td style="text-align: center;"><b>2</b></td> </tr> </table>	<b>Certified</b>	<b>CRL</b>		<b>2</b>
<b>Certified</b>	<b>CRL</b>							
	<b>2</b>							
<u>SYSTEM INFORMATION</u>		<u>TESTING DETAILS</u>						
<u>MINIMUM SYSTEM INFORMATION</u> Minimum System: DQ965GFE Serial Number: BQGF62300125 Board Revision: D41676-301 Post Memory Count: 1024 Processor Code: P4 3.6Ghz 800Mhz Bios at time of test: C096510J.86A.3736.2006.0525.1407 MCFT Memory Count 1015M Max_HDD_Man: Max_HDD_Cap: Max_HDD_Ser:		55°C Temperature: Standard Voltage Start Date: 10/19/2006 Stop Date: 10/20/2006 Insertion Test: Pass SPD Check: Pass MCFT Min: Pass MCFT Max: Pass S3 Test: N/A Power Cycle Test: N/A Power Cycle Time: OS: N/A Service Pack: N/A Test Version: MCFT 2.24						
<u>MAXIMUM SYSTEM INFORMATION</u> Maximum System: DQ965GFE Serial Number: BQGF62300138 Board Revision: D41676-301 Post Memory Count: 4096 Processor Code: P4 3.6Ghz 800Mhz Bios at time of test: C096510J.86A.3736.2006.0525.1407 MCFT Memory Count 4G 768M Max_HDD_Man: Max_HDD_Cap: Max_HDD_Ser:								
<u>VENDOR CONTACT INFORMATION</u>								
Contact: Tim Juarez		Contact Phone:		Purchase Order #:				
Test Traveler Notes:			CMTL USE ONLY:					
			Verified by:					
			Emailed by:					

Test Technician: Thanh Nguyen

In the event of a module failure, CMTL is not required to provide root cause analysis. Accuracy of testing is restricted to the above mentioned module with specific DRAM, PCB and other components as listed and tested with the CMTL Memory Compatibility Functionality Test, Microsoft Advanced Server 2000®, Windows NT 4.0 Enterprise Edition®, Windows XP®, Windows 98 SE®, Dos 6.22®, MSTRESS® (v x.x), XLINEAR® (v x.xx), FXLINEAR® (v x.xx), Patin® (v x.x), WinMTA® (v x.xx). (Voltage margining applied only to those systems that are applicable.)

[WWW.CMTLABS.COM](http://WWW.CMTLABS.COM)