




Computer Memory Test Labs Final Report

| <u>MOTHERBOARD</u> | <u>MANUFACTURER</u> | <u>CHIPSET</u> | <u>TEST NUMBER</u> | <u>TEST STATUS</u> | | |
|---|---------------------|---|--|--|----------------------|--|
| D945GCL | Intel | Intel D945G Express | 012904 | PASSED | | |
| MODULE INFORMATION | | | | Compatibility Ranking Level | | |
| Manufacturer Name: Ventura Technology Group Part #: D2-51CD63LV-555 MB: 512MB Config: 64M x 64 DRAM: Elpida DRAM Part #: EDE5108AGBG-6E-E rev G PCB Part: D2U72F na PCB_layer_count: 6 Layer Module Info: Unbuffered Non-ECC 667Mhz | | | Cas Latency: 5 Dual Die Package: <input type="checkbox"/> Env. Code RoHS Bank: 1 Assembly Type: Single Board/Non Stacked DDR2 DIMM | <table border="1" style="width: 100%;"> <tr> <td style="text-align: center;">Certified CRL</td> </tr> <tr> <td style="text-align: center;"> 4</td> </tr> </table> | Certified CRL |  4 |
| Certified CRL | | | | | | |
|  4 | | | | | | |
| SYSTEM INFORMATION | | TESTING DETAILS | | | | |
| MINIMUM SYSTEM INFORMATION Minimum System: D945GCL Serial Number: BTCL6340000B Board Revision: D67193-201 Post Memory Count: 512 Processor Code: P4 3.4Ghz 800Mhz Bios at time of test: CL94510J.86A.0008.2006.0816.1736 MCFT Memory Count 503M Max_HDD_Man: Max_HDD_Cap: Max_HDD_Ser: | | 55°C Temperature: Standard Voltage Start Date: 12/13/2006 Stop Date: 12/14/2006 Insertion Test: Pass SPD Check: Pass MCFT Min: Pass MCFT Max: Pass S3 Test: Pass Power Cycle Test: Pass Power Cycle Time: 35 OS: Windows XP Service Pack: 2 Test Version: MCFT 2.24 | | | | |
| MAXIMUM SYSTEM INFORMATION Maximum System: D945GCL Serial Number: BTCL6340000D Board Revision: D67193-201 Post Memory Count: 1024 Processor Code: P4 3.4Ghz 800Mhz Bios at time of test: CL94510J.86A.0008.2006.0816.1736 MCFT Memory Count 1015M Max_HDD_Man: Max_HDD_Cap: Max_HDD_Ser: | | | | | | |
| VENDOR CONTACT INFORMATION | | | | | | |
| Contact: Sam Lewis | | Contact Phone: (805) 581-0800 | | Purchase Order #: n/a | | |
| Test Traveler Notes: | | | CMTL USE ONLY: | | | |
| | | | Verified by: | | | |
| | | | Emailed by: | | | |

Test Technician: Thanh Nguyen

In the event of a module failure, CMTL is not required to provide root cause analysis. Accuracy of testing is restricted to the above mentioned module with specific DRAM, PCB and other components as listed and tested with the CMTL Memory Compatibility Functionality Test, Microsoft Advanced Server 2000®, Windows NT 4.0 Enterprise Edition®, Windows XP®, Windows 98 SE®, Dos 6.22®, MSTRESS® (v x.xx), XLINEAR® (v x.xx), FXLINEAR® (v x.xx), Patin® (v x.x), WinMTA® (v x.xx). (Voltage margining applied only to those systems that are applicable.)

WWW.CMTLABS.COM