

Computer Memory Test Labs Final Report

<u>MOTHERBOARD</u>	<u>MANUFACTURER</u>	<u>CHIPSET</u>	<u>TEST NUMBER</u>	<u>TEST STATUS</u>
DQ965GFE	Intel	Intel® G965	012976	PASSED
<u>MODULE INFORMATION</u>				<u>Compatibility Ranking Level</u>
Manufacturer Name: Ventura Technology Group Part #: D2-53CD64SV-555 MB: 1GB Config: 128M x 64 DRAM: Samsung DRAM Part #: K4T51083QC-ZCE6 rev C PCB Part: D2U72G rev 1.0 PCB_layer_count: 6 Layer Module Info: Unbuffered Non-ECC 667Mhz			<div style="border: 1px solid black; padding: 5px; display: inline-block;"> Certified CRL 21 </div> Cas Latency: 5 Dual Die Package: <input type="checkbox"/> Env. Code Lead-Free Bank: 2 Assembly Type: Single Board/Non Stacked DDR2 DIMM	
<u>SYSTEM INFORMATION</u>		<u>TESTING DETAILS</u>		
<u>MINIMUM SYSTEM INFORMATION</u> Minimum System: DQ965GFE Serial Number: BQGF62300107 Board Revision: D41676-301 Post Memory Count: 1024 Processor Code: P4 3.6Ghz 800Mhz Bios at time of test: C096510J.86A.3736.2006.0525.1407 MCFT Memory Count 1015M Max_HDD_Man: Max_HDD_Cap: Max_HDD_Ser:		55°C Temperature: Standard Voltage Start Date: 5/16/2007 Stop Date: 5/17/2007 Insertion Test: SPD Check: Pass MCFT Min: Pass MCFT Max: Pass S3 Test: Pass Power Cycle Test: Pass Power Cycle Time: 33 OS: Windows XP Service Pack: 2 Test Version: MCFT 2.24		
<u>MAXIMUM SYSTEM INFORMATION</u> Maximum System: DQ965GFE Serial Number: BQGF62300124 Board Revision: D41676-301 Post Memory Count: 4096 Processor Code: P4 3.6Ghz 800Mhz Bios at time of test: C096510J.86A.3736.2006.0525.1407 MCFT Memory Count 4G 768M Max_HDD_Man: Max_HDD_Cap: Max_HDD_Ser:				
<u>VENDOR CONTACT INFORMATION</u>				
Contact: Sam Lewis		Contact Phone: (805) 581-0800		Purchase Order #:
Test Traveler Notes:			CMTL USE ONLY:	
			Verified by:	
			Emailed by:	

Test Technician: Thanh Nguyen

In the event of a module failure, CMTL is not required to provide root cause analysis. Accuracy of testing is restricted to the above mentioned module with specific DRAM, PCB and other components as listed and tested with the CMTL Memory Compatibility Functionality Test, Microsoft Advanced Server 2000®, Windows NT 4.0 Enterprise Edition®, Windows XP®, Windows 98 SE®, Dos 6.22®, MSTRESS® (v x.xx), XLINEAR® (v x.xx), FXLINEAR® (v x.xx), Patin® (v x.x), WinMTA® (v x.xx). (Voltage margining applied only to those systems that are applicable.)

WWW.CMTLABS.COM