

Computer Memory Test Labs Final Report

<u>MOTHERBOARD</u>	<u>MANUFACTURER</u>	<u>CHIPSET</u>	<u>TEST NUMBER</u>	<u>TEST STATUS</u>		
D946GZIS	Intel	Intel 946GZ Express	013020	PASSED		
MODULE INFORMATION				Compatibility Ranking Level		
Manufacturer Name: Ventura Technology Group Part #: D2-53CD64SV-555 MB: 1GB Config: 128M x 64 DRAM: Samsung DRAM Part #: K4T51083QC-ZCE6 rev C PCB Part: D2U72G rev 1.0 PCB_layer_count: 6 Layer Module Info: Unbuffered Non-ECC 667Mhz			<table border="1" style="float: right; margin-left: auto;"> <tr> <td style="text-align: center;">Certified CRL</td> </tr> <tr> <td style="text-align: center;"> 18</td> </tr> </table> Cas Latency: 5 Dual Die Package: <input type="checkbox"/> Env. Code Lead-Free Bank: 2 Assembly Type: Single Board/Non Stacked DDR2 DIMM		Certified CRL	18
Certified CRL						
18						
SYSTEM INFORMATION		TESTING DETAILS				
MINIMUM SYSTEM INFORMATION Minimum System: D946GZIS Serial Number: LAIS62118885 Board Revision: D45436-300 Post Memory Count: 1024 Processor Code: P4 3.6Ghz 800Mhz Bios at time of test: TS94610J.86A.001.2006.0510.1214 MCFT Memory Count 1015M Max_HDD_Man: Max_HDD_Cap: Max_HDD_Ser:		55°C Temperature: Standard Voltage Start Date: 1/8/2007 Stop Date: 1/9/2007 Insertion Test: Pass SPD Check: Pass MCFT Min: Pass MCFT Max: Pass S3 Test: Pass Power Cycle Test: Pass Power Cycle Time: 45 OS: Windows XP Service Pack: 2 Test Version: MCFT V2.24				
MAXIMUM SYSTEM INFORMATION Maximum System: D946GZIS Serial Number: LAIS62118980 Board Revision: D45436-300 Post Memory Count: 2048 Processor Code: P4 3.6Ghz 800Mhz Bios at time of test: TS94610J.86A.001.2006.0510.1214 MCFT Memory Count 1G 1015M Max_HDD_Man: Max_HDD_Cap: Max_HDD_Ser:						
VENDOR CONTACT INFORMATION						
Contact: Sam Lewis		Contact Phone: (805) 581-0800		Purchase Order #: n/a		
Test Traveler Notes:			CMTL USE ONLY:			
			Verified by:			
			Emailed by:			

Test Technician: Thanh Nguyen

In the event of a module failure, CMTL is not required to provide root cause analysis. Accuracy of testing is restricted to the above mentioned module with specific DRAM, PCB and other components as listed and tested with the CMTL Memory Compatibility Functionality Test, Microsoft Advanced Server 2000®, Windows NT 4.0 Enterprise Edition®, Windows XP®, Windows 98 SE®, Dos 6.22®, MSTRESS® (v x.xx), XLINEAR® (v x.xx), FXLINEAR® (v x.xx), Patin® (v x.x), WinMTA® (v x.xx). (Voltage margining applied only to those systems that are applicable.)

WWW.CMTLABS.COM