




Computer Memory Test Labs Final Report

<u>MOTHERBOARD</u>	<u>MANUFACTURER</u>	<u>CHIPSET</u>	<u>TEST NUMBER</u>	<u>TEST STATUS</u>				
D946GZTS	Intel	Intel 946GZ	013152	PASSED				
<u>MODULE INFORMATION</u>				<u>Compatibility Ranking Level</u>				
Manufacturer Name: ATP Electronics Part #: AJ64K64D8BHE6S MB: 512MB Config: 64M x 64 DRAM: Samsung DRAM Part #: K4T51083QE-ZCE6 rev E PCB Part: D2U64D na PCB_layer_count: 6 Layer Module Info: Unbuffered Non-ECC 667Mhz			Cas Latency: 5 Dual Die Package: <input type="checkbox"/> Env. Code RoHS Bank: 1 Assembly Type: Single Board/Non Stacked DDR2 DIMM	<table border="1" style="margin: auto;"> <tr> <td style="text-align: center;">Certified</td> <td style="text-align: center;">CRL</td> </tr> <tr> <td style="text-align: center;"></td> <td style="text-align: center;">17</td> </tr> </table>	Certified	CRL		17
Certified	CRL							
	17							
<u>SYSTEM INFORMATION</u>		<u>TESTING DETAILS</u>						
<u>MINIMUM SYSTEM INFORMATION</u> Minimum System: D946GZTS Serial Number: AZTS62800023 Board Revision: D43871-400 Post Memory Count: 512 Processor Code: P4 3.6Ghz 800Mhz Bios at time of test: TS94610J.86A.0025.2006.0703.1026 MCFT Memory Count 503M Max_HDD_Man: Max_HDD_Cap: Max_HDD_Ser:		55°C Temperature: Standard Voltage Start Date: 2/12/2007 Stop Date: 2/14/2007 Insertion Test: Pass SPD Check: Pass MCFT Min: Pass MCFT Max: Pass S3 Test: Pass Power Cycle Test: Pass Power Cycle Time: 38 OS: Windows XP Service Pack: 2 Test Version: MCFT 2.24						
<u>MAXIMUM SYSTEM INFORMATION</u> Maximum System: D946GZTS Serial Number: AZTS62800023 Board Revision: D43871-400 Post Memory Count: 1024 Processor Code: P4 3.6Ghz 800Mhz Bios at time of test: TS94610J.86A.0025.2006.0703.1026 MCFT Memory Count 1015M Max_HDD_Man: Max_HDD_Cap: Max_HDD_Ser:								
<u>VENDOR CONTACT INFORMATION</u>								
Contact: Louis Lau		Contact Phone: (408) 732-5000 x 5		Purchase Order #:				
Test Traveler Notes:			CMTL USE ONLY:					
			Verified by: Emailed by:					

Test Technician: Thanh Nguyen

In the event of a module failure, CMTL is not required to provide root cause analysis. Accuracy of testing is restricted to the above mentioned module with specific DRAM, PCB and other components as listed and tested with the CMTL Memory Compatibility Functionality Test, Microsoft Advanced Server 2000®, Windows NT 4.0 Enterprise Edition®, Windows XP®, Windows 98 SE®, Dos 6.22®, MSTRESS® (v x.x), XLINEAR® (v x.xx), FXLINEAR® (v x.xx), Patin® (v x.x), WinMTA® (v x.xx). (Voltage margining applied only to those systems that are applicable.)

WWW.CMTLABS.COM