




Computer Memory Test Labs Final Report

<u>MOTHERBOARD</u>	<u>MANUFACTURER</u>	<u>CHIPSET</u>	<u>TEST NUMBER</u>	<u>TEST STATUS</u>				
DQ965CO	Intel	Intel® G965	013181	PASSED				
MODULE INFORMATION				Compatibility Ranking Level				
Manufacturer Name: ATP Electronics Part #: AJ28K64E8BHE6S MB: 1GB Config: 128M x 64 DRAM: Samsung DRAM Part #: K4T51083QE-ZCE6 rev E PCB Part: SJ240E08K1 na PCB_layer_count: 6 Layer Module Info: Unbuffered Non-ECC 667Mhz			Cas Latency: 5 Dual Die Package: <input type="checkbox"/> Env. Code RoHS Bank: 2 Assembly Type: Single Board/Non Stacked DDR2 DIMM	<table border="1" style="margin: auto;"> <tr> <td style="text-align: center;">Certified CRL</td> <td style="text-align: center;">14</td> </tr> <tr> <td colspan="2" style="text-align: center;"></td> </tr> </table>	Certified CRL	14		
Certified CRL	14							
								
SYSTEM INFORMATION		TESTING DETAILS						
MINIMUM SYSTEM INFORMATION Minimum System: DQ965CO Serial Number: AZCO62700362 Board Revision: D37070-401 Post Memory Count: 1024 Processor Code: P4 3.6Ghz 800Mhz Bios at time of test: CO96510J.86A.3950.2006.0613.1125 MCFT Memory Count 1007M Max_HDD_Man: Max_HDD_Cap: Max_HDD_Ser:		55°C Temperature: Standard Voltage Start Date: 2/7/2007 Stop Date: 2/8/2007 Insertion Test: Pass SPD Check: Pass MCFT Min: Pass MCFT Max: Pass S3 Test: Pass Power Cycle Test: Pass Power Cycle Time: 30 OS: Windows XP Service Pack: 2 Test Version: MCFT 2.24						
MAXIMUM SYSTEM INFORMATION Maximum System: DQ965CO Serial Number: AZCO62700367 Board Revision: D37070-401 Post Memory Count: 4096 Processor Code: P4 3.6Ghz 800Mhz Bios at time of test: CO96510J.86A.3950.2006.0613.1125 MCFT Memory Count 4G 704M Max_HDD_Man: Max_HDD_Cap: Max_HDD_Ser:								
VENDOR CONTACT INFORMATION								
Contact: Louis Lau		Contact Phone: (408) 732-5000 x 5		Purchase Order #:				
Test Traveler Notes:			CMTL USE ONLY:					
			Verified by:					
			Emailed by:					

Test Technician: Thanh Nguyen

In the event of a module failure, CMTL is not required to provide root cause analysis. Accuracy of testing is restricted to the above mentioned module with specific DRAM, PCB and other components as listed and tested with the CMTL Memory Compatibility Functionality Test, Microsoft Advanced Server 2000®, Windows NT 4.0 Enterprise Edition®, Windows XP®, Windows 98 SE®, Dos 6.22®, MSTRESS® (v x.x), XLINEAR® (v x.xx), FXLINEAR® (v x.xx), Patin® (v x.x), WinMTA® (v x.xx). (Voltage margining applied only to those systems that are applicable.)

WWW.CMTLABS.COM