

Computer Memory Test Labs Final Report

<u>MOTHERBOARD</u>	<u>MANUFACTURER</u>	<u>CHIPSET</u>	<u>TEST NUMBER</u>	<u>TEST STATUS</u>		
D975XBX	Intel	Intel D975X	013907	PASSED		
<u>MODULE INFORMATION</u>				<u>Compatibility Ranking Level</u>		
Manufacturer Name: Smart Modular Technologies Part #: SG2566UDR212852IB MB: 2GB Config: 256M x 64 DRAM: Qimonda DRAM Part #: HYB18T1G800BF-3S rev B PCB Part: PG58G240LUBUB1RE rev B PCB_layer_count: 8 Layer Module Info: Unbuffered Non-ECC 667Mhz			Cas Latency: 5 Dual Die Package: <input type="checkbox"/> Env. Code RoHS Bank: 2 Assembly Type: Single Board/Non Stacked DDR2 DIMM	<table border="1" style="width: 100%;"> <tr> <td style="text-align: center;">Certified CRL</td> </tr> <tr> <td style="text-align: center;"> 7</td> </tr> </table>	Certified CRL	7
Certified CRL						
7						
<u>SYSTEM INFORMATION</u>		<u>TESTING DETAILS</u>				
<u>MINIMUM SYSTEM INFORMATION</u> Minimum System: D975XBX Serial Number: BQBX54700097 Board Revision: D27094-203 Post Memory Count: 2048 Processor Code: P4 3.2Ghz 800Mhz Bios at time of test: BX97510J.86A.1474 MCFT Memory Count 1G 1023M Max_HDD_Man: Max_HDD_Cap: Max_HDD_Ser:		55°C Temperature: Standard Voltage Start Date: 5/23/2007 Stop Date: 5/24/2007 Insertion Test: SPD Check: Pass MCFT Min: Pass MCFT Max: Pass S3 Test: Pass Power Cycle Test: Pass Power Cycle Time: 32 OS: Windows XP Service Pack: 2 Test Version: MCFT 2.24				
<u>MAXIMUM SYSTEM INFORMATION</u> Maximum System: D975XBX Serial Number: BQBX54700100 Board Revision: D27094-203 Post Memory Count: 8192 Processor Code: P4 3.2Ghz 800Mhz Bios at time of test: BX97510J.86A.1474 MCFT Memory Count 8G 768M Max_HDD_Man: Max_HDD_Cap: Max_HDD_Ser:						
<u>VENDOR CONTACT INFORMATION</u>						
Contact: Jim Schwarz		Contact Phone:		Purchase Order #: 05/15/2007		
Test Traveler Notes:			CMTL USE ONLY:			
			Verified by:			
			Emailed by:			

Test Technician: Thanh Nguyen

In the event of a module failure, CMTL is not required to provide root cause analysis. Accuracy of testing is restricted to the above mentioned module with specific DRAM, PCB and other components as listed and tested with the CMTL Memory Compatibility Functionality Test, Microsoft Advanced Server 2000®, Windows NT 4.0 Enterprise Edition®, Windows XP®, Windows 98 SE®, Dos 6.22®, MSTRESS® (v x.xx), XLINEAR® (v x.xx), FXLINEAR® (v x.xx), Patin® (v x.x), WinMTA® (v x.xx). (Voltage margining applied only to those systems that are applicable.)

WWW.CMTLABS.COM