

Computer Memory Test Labs Final Report

<u>MOTHERBOARD</u>	<u>MANUFACTURER</u>	<u>CHIPSET</u>	<u>TEST NUMBER</u>	<u>TEST STATUS</u>		
(DG33BU)/DP35DP/DG33FB	Intel	Intel® G33	015674	PASSED		
MODULE INFORMATION						
Manufacturer Name: Buffalo Part #: D2U800CX-1GEJJ MB: 1GB Config: 128M x 64 DRAM: Elpida DRAM Part #: E5108AJBG-8E-E rev J PCB Part: 2D286NF3-AB PCB_layer_count: 6 Layer Module Info: Unbuffered Non-ECC 800Mhz			Module ID: BUF252 Cas Latency: 5 Dual Die Package: <input type="checkbox"/> Env. Code RoHS Bank: 2 Assembly Type: Single Board/Non Stacked DDR2 DIMM	Compatibility Ranking Level <table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: center;">Certified CRL</td> <td style="text-align: center;">2</td> </tr> </table>	Certified CRL	2
Certified CRL	2					
SYSTEM INFORMATION		TESTING DETAILS				
MINIMUM SYSTEM INFORMATION Minimum System: (DG33BU)/DP35DP/DG33FB Serial Number: AZBU71800727 Board Revision: D79951-405 Post Memory Count: 1024 Processor Code: Intel® Core™2 Duo,6420,2.13GHz,1066F Bios at time of test: DPP3510J.86A.0297.2007.1022.2244 MCFT Memory Count: 1004M 128K Max_HDD_Man: Max_HDD_Cap: Max_HDD_Ser:		55°C Temperature: Standard Voltage Start Date: 8/5/2008 Stop Date: 8/6/2008 Insertion Test: SPD Check: Pass MCFT Min: Pass MCFT Max: Pass S3 Test: Pass Power Cycle Test: N/A Power Cycle Time: OS: Service Pack: N/A Test Version: R.S.T PRO v2.81				
MAXIMUM SYSTEM INFORMATION Maximum System: (DG33BU)/DP35DP/DG33FB Serial Number: AZBU718007TN Board Revision: D79951-405 Post Memory Count: 4096 Processor Code: Intel® Core™2 Duo,6420,2.13GHz,1066F Bios at time of test: DPP3510J.86A.0297.2007.1022.2244 MCFT Memory Count: 4G 704M Max_HDD_Man: Max_HDD_Cap: Max_HDD_Ser:						
VENDOR CONTACT INFORMATION						
Contact: Bruce Reilly	Contact Phone:	Purchase Order #:				
Test Traveler Notes:			CMTL USE ONLY:			
			Verified by: Emailed by:			

Test Technician: Thanh Nguyen

In the event of a module failure, CMTL is not required to provide root cause analysis. Accuracy of testing is restricted to the above mentioned module with specific DRAM, PCB and other components as listed and tested with the CMTL Memory Compatibility Functionality Test, Microsoft Advanced Server 2000®, Windows NT 4.0 Enterprise Edition®, Windows XP®, Windows 98 SE®, Dos 6.22®, MSTRESS® (v x.x), XLINEAR® (v x.xx), FXLINEAR® (v x.xx), Patin® (v x.x), WinMTA® (v x.xx). (Voltage margining applied only to those systems that are applicable.)

WWW.CMTLABS.COM