

# Computer Memory Test Labs Final Report

<u>MOTHERBOARD</u>	<u>MANUFACTURER</u>	<u>CHIPSET</u>	<u>TEST NUMBER</u>	<u>TEST STATUS</u>
DX48BT2	Intel	Intel® X48	015918	PASSED
<b>MODULE INFORMATION</b> <span style="float: right;"><b>Compatibility Ranking Level</b></span>				
Manufacturer Name: <b>Wintec Industries</b>		Module ID: <b>WTC102</b>		<div style="display: flex; justify-content: space-between; align-items: center;"> <span><b>Certified CRL</b></span> <span><b>2</b></span> </div>
Part #: <b>3DU3294D-13</b>	MB: <b>2GB</b>	Config: <b>256M x 64</b>	Cas Latency: <b>9</b>	
DRAM: <b>Samsung</b>	DRAM Part #: <b>K4B1G0846D-HCH9 rev D</b>		Dual Die Package: <input type="checkbox"/>	
PCB Part: <b>B63URCB 0.70</b>	PCB_layer_count: <b>6 Layer</b>		Env. Code <b>RoHS</b>	
Module Info: <b>Unbuffered Non-ECC 1333MHz</b>	Assembly Type: <b>Single Board/Non Stacked</b>		Bank: <b>2</b>	
<b>SYSTEM INFORMATION</b>		<b>TESTING DETAILS</b>		
<b>MINIMUM SYSTEM INFORMATION</b> Minimum System: DX48BT2 Serial Number: BQBQ8070001Y Board Revision: E26191-201 Post Memory Count: 2048 Processor Code: Intel® Core™2 Duo,E6850,3.00GHz,1333 Bios at time of test: BTX3810J.86A.1814 MCFT Memory Count: 2027M 816K Max_HDD_Man: Max_HDD_Cap: Max_HDD_Ser:		55°C Temperature: Standard Voltage Start Date: 11/5/2008 Stop Date: 11/6/2008 Insertion Test: SPD Check: Pass MCFT Min: Pass MCFT Max: Pass S3 Test: Pass Power Cycle Test: N/A Power Cycle Time: OS: N/A Service Pack: N/A Test Version: R.S.T PRO v2.81		
<b>MAXIMUM SYSTEM INFORMATION</b> Maximum System: DX48BT2 Serial Number: BQBQ80700011 Board Revision: E26191-201 Post Memory Count: 8192 Processor Code: Intel® Core™2 Duo,E6850,3.00GHz,1333 Bios at time of test: BTX3810J.86A.1814 MCFT Memory Count: 8G 768M Max_HDD_Man: Max_HDD_Cap: Max_HDD_Ser:				
<b>VENDOR CONTACT INFORMATION</b>				
Contact: Litton Chen	Contact Phone: 408 856-0912	Purchase Order #:		
Test Traveler Notes:			CMTL USE ONLY:	
			Verified by:	
			Emailed by:	

Test Technician: Thanh Nguyen

In the event of a module failure, CMTL is not required to provide root cause analysis. Accuracy of testing is restricted to the above mentioned module with specific DRAM, PCB and other components as listed and tested with the CMTL Memory Compatibility Functionality Test, Microsoft Advanced Server 2000®, Windows NT 4.0 Enterprise Edition®, Windows XP®, Windows 98 SE®, Dos 6.22®, MSTRESS® (v x.x), XLINEAR® (v x.xx), FXLINEAR® (v x.xx), Patin® (v x.x), WinMTA® (v x.xx). (Voltage margining applied only to those systems that are applicable.)

[WWW.CMTLABS.COM](http://WWW.CMTLABS.COM)