

Computer Memory Test Labs Final Report

<u>MOTHERBOARD</u>	<u>MANUFACTURER</u>	<u>CHIPSET</u>	<u>TEST NUMBER</u>	<u>TEST STATUS</u>				
DX58SO	Intel	Intel® X58	016062	PASSED				
MODULE INFORMATION				Compatibility Ranking Level				
Manufacturer Name: Wintec Industries		Module ID: WTC101	<table border="1" style="margin: auto;"> <tr> <td style="text-align: center;">Certified CRL</td> <td style="text-align: center;">3</td> </tr> <tr> <td colspan="2" style="text-align: center;">  </td> </tr> </table>		Certified CRL	3		
Certified CRL	3							
								
Part #: 3DU3184D-13	MB: 1GB	Config: 128M x 64	Cas Latency: 9					
DRAM: Samsung	DRAM Part #: K4B1G0846D-HCH9 rev D	PCB Part: B63URCA 0.71	Dual Die Package: <input type="checkbox"/>	Env. Code RoHS				
PCB_layer_count: 6 Layer	Module Info: Unbuffered Non-ECC 1333MHz	Assembly Type: Single Board/Non Stacked	Bank: 1					
SYSTEM INFORMATION		TESTING DETAILS						
MINIMUM SYSTEM INFORMATION Minimum System: DX58SO Serial Number: USSO8410014N Board Revision: E29331-402 Post Memory Count: 1024MB Processor Code: Intel® CPU 000 @ 3.20GHz, 6.400 GT/s Bios at time of test: SOX5810J.86A.2747 MCFT Memory Count: 971M 740K Max_HDD_Man: Max_HDD_Cap: Max_HDD_Ser:		55°C Temperature: Standard Voltage Start Date: 12/5/2008 Stop Date: 12/8/2008 Insertion Test: SPD Check: Pass MCFT Min: Pass MCFT Max: Pass S3 Test: Pass Power Cycle Test: N/A Power Cycle Time: OS: N/A Service Pack: N/A Test Version: RST PRO V2.81						
MAXIMUM SYSTEM INFORMATION Maximum System: DX58SO Serial Number: USSO833000FT Board Revision: E29331-402 Post Memory Count: 3072MB Processor Code: Intel® CPU 000 @ 3.20GHz, 6.400 GT/s Bios at time of test: SOX5810J.86A.2747 MCFT Memory Count: 3018M 176K Max_HDD_Man: Max_HDD_Cap: Max_HDD_Ser:								
VENDOR CONTACT INFORMATION								
Contact: Matthew Gallagher	Contact Phone: (408) 856-0657	Purchase Order #: Litton Chen						
Test Traveler Notes:			CMTL USE ONLY:					
			Verified by:					
			Emailed by:					

Test Technician: Thanh Nguyen

In the event of a module failure, CMTL is not required to provide root cause analysis. Accuracy of testing is restricted to the above mentioned module with specific DRAM, PCB and other components as listed and tested with the CMTL Memory Compatibility, Functionality Test, Microsoft Advanced Server 2000®, Windows NT 4.0 Enterprise Edition®, Windows XP®, Windows 98 SE®, Dos 6.22®, MSTRESS® (v x.x), XLINEAR® (v x.xx), FXLINEAR® (v x.xx), Patin® (v x.x), WinMTA® (v x.xx). (Voltage margining applied only to those systems that are applicable.)

WWW.CMTLABS.COM