

# Computer Memory Test Labs Final Report

<u>MOTHERBOARD</u>	<u>MANUFACTURER</u>	<u>CHIPSET</u>	<u>TEST NUMBER</u>	<u>TEST STATUS</u>
D5400XS	Intel	Intel® 5400	016077	PASSED
<b>MODULE INFORMATION</b> <span style="float: right;"><b>Compatibility Ranking Level</b></span>				
Manufacturer Name: <b>Swissbit</b>		Module ID: <b>SWS030</b>		<div style="display: flex; justify-content: space-between; align-items: center;"> <span><b>Certified CRL</b></span> <span><b>2</b></span> </div>
Part #: <b>MEF51272B1AC2EP-2ARE</b>				
MB: <b>4GB</b>				
Config: <b>512M x 72</b>		Cas Latency: <b>5</b>		
DRAM: <b>Elpida</b>		Dual Die Package: <input type="checkbox"/>		
DRAM Part #: <b>EDE1104ACSE-8E-E rev C</b>		Env. Code <b>RoHS</b>		
PCB Part: <b>BA2FRCU 3.10</b>		Bank: <b>2</b>		
PCB_layer_count: <b>10 Layer</b>		Assembly Type: <b>Single Board/Non Stacked</b>		
Module Info: <b>Buffered</b>		<b>ECC</b>		<b>800Mhz</b>
		<b>FB-DIMM</b>		
<b>SYSTEM INFORMATION</b>		<b>TESTING DETAILS</b>		
<b>MINIMUM SYSTEM INFORMATION</b> Minimum System: D5400XS Serial Number: AZXS80200003 Board Revision: D94664-400 Post Memory Count: 4096MB Processor Code: Intel® Xeon®, Quad,X5472,3.0GHz,1600 Bios at time of test: XS54010J.86A.1149 MCFT Memory Count: 4G 768M Max_HDD_Man: Max_HDD_Cap: Max_HDD_Ser:		55°C Temperature: Standard Voltage Start Date: 12/18/2008 Stop Date: 12/19/2008 Insertion Test: SPD Check: Pass MCFT Min: Pass MCFT Max: Pass S3 Test: Pass Power Cycle Test: N/A Power Cycle Time: OS: N/A Service Pack: N/A Test Version: R.S.T PRO v2.81		
<b>MAXIMUM SYSTEM INFORMATION</b> Maximum System: D5400XS Serial Number: AZXS80200015 Board Revision: D94664-400 Post Memory Count: 16384MB Processor Code: Intel® Xeon®, Quad,X5472,3.0GHz,1600 Bios at time of test: XS54010J.86A.1149 MCFT Memory Count: 16G 768M Max_HDD_Man: Max_HDD_Cap: Max_HDD_Ser:				
<b>VENDOR CONTACT INFORMATION</b>				
Contact: Placeholder		Contact Phone:		Purchase Order #: CMTL_11122008_2
Test Traveler Notes:			CMTL USE ONLY:	
			Verified by:	
			Emailed by:	

Test Technician: Thanh Nguyen

In the event of a module failure, CMTL is not required to provide root cause analysis. Accuracy of testing is restricted to the above mentioned module with specific DRAM, PCB and other components as listed and tested with the CMTL Memory Compatibility Functionality Test, Microsoft Advanced Server 2000®, Windows NT 4.0 Enterprise Edition®, Windows XP®, Windows 98 SE®, Dos 6.22®, MSTRESS® (v x.x), XLINEAR® (v x.xx), FXLINEAR® (v x.xx), Patin® (v x.x), WinMTA® (v x.xx). (Voltage margining applied only to those systems that are applicable.)

[WWW.CMTLABS.COM](http://WWW.CMTLABS.COM)