

Computer Memory Test Labs Final Report

<u>MOTHERBOARD</u>	<u>MANUFACTURER</u>	<u>CHIPSET</u>	<u>TEST NUMBER</u>	<u>TEST STATUS</u>
DG41TY	Intel	Intel® G41	016366	PASSED
MODULE INFORMATION				Compatibility Ranking Level
Manufacturer Name: Buffalo		Module ID: BUF253		<div style="display: flex; justify-content: space-between;"> Certified CRL 13 </div>
Part #:	D2U800CX-2GECJ			
MB:	2GB			
Config:	256M x 64	Cas Latency: 5		
DRAM:	Elpida	Dual Die Package: <input type="checkbox"/>		
DRAM Part #:	E1108ACBG-8E-E rev C	Env. Code RoHS		
PCB Part:	2D286NF3-AB	Bank: 2		
PCB_layer_count:	6 Layer	Assembly Type: Single Board/Non Stacked		
Module Info:	Unbuffered	Non-ECC	800Mhz	DDR2 DIMM
SYSTEM INFORMATION		TESTING DETAILS		
MINIMUM SYSTEM INFORMATION		55°C Temperature: Standard Voltage Start Date: 2/4/2009 Stop Date: 2/5/2009 Insertion Test: SPD Check: Pass MCFT Min: Pass MCFT Max: Pass S3 Test: Pass Power Cycle Test: N/A Power Cycle Time: OS: N/A Service Pack: N/A Test Version: RST PRO V2.81		
Minimum System:	DG41TY			
Serial Number:	AZTY840000BE			
Board Revision:	E47335-200			
Post Memory Count:	2048			
Processor Code:	Intel® 2160,1.8GHz,800FSB			
Bios at time of test:	TYG4110H.86A.00808			
MCFT Memory Count:	2008M 904K			
Max_HDD_Man:				
Max_HDD_Cap:				
Max_HDD_Ser:				
MAXIMUM SYSTEM INFORMATION				
Maximum System:	DG41TY			
Serial Number:	AZTY840000BF			
Board Revision:	E47335-200			
Post Memory Count:	4096			
Processor Code:	Intel® 2160,1.8GHz,800FSB			
Bios at time of test:	TYG4110H.86A.00808			
MCFT Memory Count:	5G			
Max_HDD_Man:				
Max_HDD_Cap:				
Max_HDD_Ser:				
VENDOR CONTACT INFORMATION				
Contact:	Bruce Reilly	Contact Phone:	Purchase Order #:	
Test Traveler Notes:			CMTL USE ONLY:	
			Verified by:	
			Emailed by:	

Test Technician: Thanh Nguyen

In the event of a module failure, CMTL is not required to provide root cause analysis. Accuracy of testing is restricted to the above mentioned module with specific DRAM, PCB and other components as listed and tested with the CMTL Memory Compatibility, Functionality Test, Microsoft Advanced Server 2000®, Windows NT 4.0 Enterprise Edition®, Windows XP®, Windows 98 SE®, Dos 6.22®, MSTRESS® (v x.x), XLINEAR® (v x.xx), FXLINEAR® (v x.xx), Patin® (v x.x), WinMTA® (v x.xx). (Voltage margining applied only to those systems that are applicable.)

WWW.CMTLABS.COM