


Computer Memory Test Labs Final Report

<u>MOTHERBOARD</u>	<u>MANUFACTURER</u>	<u>CHIPSET</u>	<u>TEST NUMBER</u>	<u>TEST STATUS</u>
DP55WB	Intel	Intel® P55	017133	PASSED
MODULE INFORMATION				Compatibility Ranking Level
Manufacturer Name: Kingston		Module ID: KIN287		Certified CRL  4
Part #: KVR1333D3N9/2G				
MB: 2GB				
Config: 256M x 64		Cas Latency: 9		
DRAM: Elpida		Dual Die Package: <input type="checkbox"/>		
DRAM Part #: EDJ1108BBSE-DJ-F rev B		Env. Code RoHS		
PCB Part: 2025403-0F1.A00 rev A, R/C B rev 0		Bank: 2		
PCB_layer_count: 6 Layer		Assembly Type: Single Board/Non Stacked		
Module Info: Unbuffered		Non-ECC 1333MHz		DDR3 DIMM
SYSTEM INFORMATION			TESTING DETAILS	
MINIMUM SYSTEM INFORMATION				
Minimum System: DP55WB		55°C Temperature: Standard Voltage		
Serial Number: AZWB9260000C		Start Date: 9/9/2009		
Board Revision: E64798-201		Stop Date: 9/10/2009		
Post Memory Count: 4096MB		Insertion Test:		
Processor Code: Intel® Core™ CPU 860 @ 2.80GHz, 64 A		SPD Check: Pass		
Bios at time of test: WBIBX10J.86A.0047.2009.0612.0128		MCFT Min: Pass		
MCFT Memory Count: 4G 768M		MCFT Max: Pass		
Max_HDD_Man:		S3 Test: Pass		
Max_HDD_Cap:		Power Cycle Test: N/A		
Max_HDD_Ser:		Power Cycle Time:		
MAXIMUM SYSTEM INFORMATION				
Maximum System: DP55WB		OS: N/A		
Serial Number: AZWB9260000E		Service Pack: N/A		
Board Revision: E64798-201		Test Version: RST Pro3 v3.02		
Post Memory Count: 8192MB				
Processor Code: Intel® Core™ CPU 860 @ 2.80GHz, 64 A				
Bios at time of test: WBIBX10J.86A.0047.2009.0612.0128				
MCFT Memory Count: 8G 768M				
Max_HDD_Man:				
Max_HDD_Cap:				
Max_HDD_Ser:				
VENDOR CONTACT INFORMATION				
Contact: Mike Mohney		Contact Phone: 714.424.3976		Purchase Order #:
Test Traveler Notes:			CMTL USE ONLY:	
			Verified by:	
			Emailed by:	

Test Technician: Thanh Nguyen

In the event of a module failure, CMTL is not required to provide root cause analysis. Accuracy of testing is restricted to the above mentioned module with specific DRAM, PCB and other components as listed and tested with the CMTL Memory Compatibility, Functionality Test, Microsoft Advanced Server 2000®, Windows NT 4.0 Enterprise Edition®, Windows XP®, Windows 98 SE®, Dos 6.22®, MSTRESS® (v x.x), XLINEAR® (v x.xx), FXLINEAR® (v x.xx), Patin® (v x.x), WinMTA® (v x.xx). (Voltage margining applied only to those systems that are applicable.)

WWW.CMTLABS.COM