

Computer Memory Test Labs Final Report

<u>MOTHERBOARD</u>	<u>MANUFACTURER</u>	<u>CHIPSET</u>	<u>TEST NUMBER</u>	<u>TEST STATUS</u>
DG41KR	Intel	Intel® G41	017185	PASSED
MODULE INFORMATION				Compatibility Ranking Level
Manufacturer Name: Kingston		Module ID: KIN283		<div style="display: flex; justify-content: space-between; align-items: center;"> Certified CRL 6 </div>
Part #: KVR1066D3N7/1G		Cas Latency: 7		
MB: 1GB		Dual Die Package: <input type="checkbox"/>		
Config: 128M x 64		Env. Code RoHS		
DRAM: Kingston		Bank: 1		
DRAM Part #: D1288JEKAPGA7U rev A		Assembly Type: Single Board/Non Stacked		
PCB Part: 2025402-0F1.C00 rev C, R/C A rev 0		DDR3 DIMM		
PCB_layer_count: 6 Layer				
Module Info: Unbuffered Non-ECC 1066MHz				
SYSTEM INFORMATION		TESTING DETAILS		
MINIMUM SYSTEM INFORMATION		55°C Temperature: Standard Voltage Start Date: 9/30/2009 Stop Date: 10/1/2009 Insertion Test: SPD Check: Pass MCFT Min: Pass MCFT Max: Pass S3 Test: Pass Power Cycle Test: N/A Power Cycle Time: OS: N/A Service Pack: N/A Test Version: RST Pro3 v3.02		
Minimum System: DG41KR				
Serial Number: BTKR9340000K				
Board Revision: E62839-300				
Post Memory Count: 1024MB				
Processor Code: Intel® Core™2 Duo,E6850,3.00GHz,1336				
Bios at time of test: KRG4110H.86A.0018				
MCFT Memory Count: 984M 456K				
Max_HDD_Man:				
Max_HDD_Cap:				
Max_HDD_Ser:				
MAXIMUM SYSTEM INFORMATION				
Maximum System: DG41KR				
Serial Number: BTKR93400002				
Board Revision: E62839-300				
Post Memory Count: 2048MB				
Processor Code: Intel® Core™2 Duo,E6850,3.00GHz,1336				
Bios at time of test: KRG4110H.86A.0018				
MCFT Memory Count: 2008M 456K				
Max_HDD_Man:				
Max_HDD_Cap:				
Max_HDD_Ser:				
VENDOR CONTACT INFORMATION				
Contact: Mike Mohney		Contact Phone: 714.424.3976		Purchase Order #:
Test Traveler Notes:			CMTL USE ONLY:	
			Verified by:	
			Emailed by:	

Test Technician: Thanh Nguyen

In the event of a module failure, CMTL is not required to provide root cause analysis. Accuracy of testing is restricted to the above mentioned module with specific DRAM, PCB and other components as listed and tested with the CMTL Memory Compatibility, Functionality Test, Microsoft Advanced Server 2000®, Windows NT 4.0 Enterprise Edition®, Windows XP®, Windows 98 SE®, Dos 6.22®, MSTRESS® (v x.x), XLINEAR® (v x.xx), FXLINEAR® (v x.xx), Patin® (v x.x), WinMTA® (v x.xx). (Voltage margining applied only to those systems that are applicable.)

WWW.CMTLABS.COM