

Computer Memory Test Labs Final Report

<u>MOTHERBOARD</u>	<u>MANUFACTURER</u>	<u>CHIPSET</u>	<u>TEST NUMBER</u>	<u>TEST STATUS</u>
DP55WB	Intel	Intel® P55	017210	PASSED
MODULE INFORMATION				Compatibility Ranking Level
Manufacturer Name: Avant Technology		Module ID: AVT276		<div style="display: flex; justify-content: space-between;"> Certified CRL 1 </div>
Part #: AVF6456U61F9333G2-MTFP				
MB: 2GB				
Config: 256M x 64		Cas Latency: 9		
DRAM: Micron		Dual Die Package: <input type="checkbox"/>		
DRAM Part #: MT41J128M8JP-15E rev F		Env. Code RoHS		
PCB Part: B63URCB 0.70, Rawcard B rev 0		Bank: 2		
PCB_layer_count: 6 Layer		Assembly Type: Single Board/Non Stacked		
Module Info: Unbuffered Non-ECC 1333MHz		DDR3 DIMM		
SYSTEM INFORMATION		TESTING DETAILS		
MINIMUM SYSTEM INFORMATION		55°C Temperature: Standard Voltage Start Date: 11/24/2009 Stop Date: 11/25/2009 Insertion Test: SPD Check: Pass MCFT Min: Pass MCFT Max: Pass S3 Test: Pass Power Cycle Test: N/A Power Cycle Time: OS: N/A Service Pack: N/A Test Version: RST Pro3 v3.02		
Minimum System: DP55WB				
Serial Number: AZWB9260000C				
Board Revision: E64798-201				
Post Memory Count: 4096MB				
Processor Code: Intel® Core™ CPU 860 @ 2.80GHz, 64 A				
Bios at time of test: WBIBX10J.86A.0047.2009.0612.0128				
MCFT Memory Count: 4G 768M				
Max_HDD_Man:				
Max_HDD_Cap:				
Max_HDD_Ser:				
MAXIMUM SYSTEM INFORMATION				
Maximum System: DP55WB				
Serial Number: AZWB9260000E				
Board Revision: E64798-201				
Post Memory Count: 8192MB				
Processor Code: Intel® Core™ CPU 860 @ 2.80GHz, 64 A				
Bios at time of test: WBIBX10J.86A.0047.2009.0612.0128				
MCFT Memory Count: 8G 768M				
Max_HDD_Man:				
Max_HDD_Cap:				
Max_HDD_Ser:				
VENDOR CONTACT INFORMATION				
Contact: Dino Roseland		Contact Phone: (512) 491-7411		Purchase Order #: AV1109
Test Traveler Notes:			CMTL USE ONLY:	
			Verified by:	
			Emailed by:	

Test Technician: Thanh Nguyen

In the event of a module failure, CMTL is not required to provide root cause analysis. Accuracy of testing is restricted to the above mentioned module with specific DRAM, PCB and other components as listed and tested with the CMTL Memory Compatibility, Functionality Test, Microsoft Advanced Server 2000®, Windows NT 4.0 Enterprise Edition®, Windows XP®, Windows 98 SE®, Dos 6.22®, MSTRESS® (v x.x), XLINEAR® (v x.xx), FXLINEAR® (v x.xx), Patin® (v x.x), WinMTA® (v x.xx). (Voltage margining applied only to those systems that are applicable.)

WWW.CMTLABS.COM